

LT6



**Compact, mobile -
on-site lighting and power**



Multiquip introduces the LT6D light tower. Its compact design simplifies mobility and provides exceptional lighting and reliable power to your work site. Its many standard features make it the ideal choice for lighting in construction, mining, oil and gas exploration, security and outdoor events.



Large door panels provide convenient access, easy operation and simplify routine maintenance.

- **Ships up to 12 units** on a standard 48' flatbed truck with a compact, small footprint design
- **Prevent engine fluids from escaping** into the environment with a tub design that offers full containment
- **Corrosion resistant** polypropylene door panels are lightweight, durable and easy to clean
- **Superior illumination** is provided by metal halide lamps enclosed in durable aluminum and steel housings that withstand harsh work environments
- **Supply power to equipment and small tools** with an externally mounted 120V duplex receptacles
- **Centralized control panel** displays breakers, hour meter, warning lights for low oil pressure and high temperature shutdowns and includes an internal compartment light
- **Minimize work area noise** with sound attenuated, weatherproof housing emitting only 68 dB(A)
- **Long running times-** up to 72.5 hours- are attainable with a fuel efficient Kohler water cooled, diesel engine and 34 gallon fuel capacity
- **Heavy-duty mast features** zinc dichromate sections for corrosion resistance deploys to a height of 32' and rotates 360°
- **Maintain stability in environments** with up to 65 MPH winds, five outrigger points provide added security

Specifications:	
Model	LT6D
Prime/Standby	6kW / 7kW
Voltage	120/240V - Single Phase - 60 Hz
Generator	Brushless, Class H, ± 6% Voltage Regulation
Generator Power	120V/50A - 240V/25A
Engine	KOHLER KDW-1003 - Electric Start
Engine Design	3-Cycle, Water Cooled, Direct Injection
EPA Certification	Tier 4 final
Sound Level	68 dB(A)
Mast	32 Ft. (Deployed) - 360° Rotation
Lamps (4)	1,000W Metal Halide - 440,000 Lumens
Wind Stability	65 MPH (All Outriggers Deployed)
External Receptacles	Duplex 120V/15A GFCI (1) NEMA L14-30 30A 125V/240V
Trailer	DOT Certified - 2,000 lb. Axle
Support Points	(5) Adjustable Jack Stands
Fuel Capacity	34 Gal. - Diesel
Run Time	72.5 Hrs. @ (3/4 Load)
Dimensions/Weight	132" x 50" x 72" / 1,575 Lbs.

Your Multiquip dealer is:

Connect with us on

