



CONCRETE. STONE. MASONRY. UNSTOPPABLE.

Bar Dimension and Cutting Depths

Saw	Bar Part Number	Segment Count	Called Length	Overall Length	Practical Cutting Depth
880F4*	529829	25 F4	10 in (25 cm)	16.7 in (42.4 cm)	11.9 in (30.3 cm)
	523080	29 F4	15 in (38 cm)	20.3 in (51.6 cm)	15.6 in (39.5 cm)
	529767	34 F4	20 in (50 cm)	24.8 in (62.9 cm)	20 in (50.8 cm)
	525320	40 F4	25 in (63 cm)	30.1 in (76.4 cm)	25.4 in (64.5 cm)
853PRO*	72269	28	11 in (28 cm)	15.1 in (38.3 cm)	10.6 in (26.9 cm)
	72176	33	15 in (38 cm)	18.8 in (47.8 cm)	14.5 in (36.2 cm)
853PRO Plus*	72177	39	19 in (48 cm)	23.2 in (58.9 cm)	18.4 in (47.9 cm)
	70646	47	24 in (60 cm)	29.1 in (73.9 cm)	24.4 in (61.9 cm)
	513553 (PRK)	29	11 in (29 cm)	15.3 in (38.9 cm)	10.3 in (26.2 cm)
814*	525741	25	13 in (32 cm)	14.9 in (37.9 cm)	12.4 in (31.4 cm)
633F4*	525872	27 F4	14 in (35 cm)	19.7 in (50.0 cm)	15.1 in (38.3 cm)
	524490	29 F4	16 in (40 cm)	21.7 in (55.1 cm)	16.9 in (42.9 cm)
633GC*	73600	32	14 in (35 cm)	19.5 in (49.5 cm)	14.3 in (36.4 cm)
	71600	35	16 in (40 cm)	21.7 (55.1 cm)	16.4 in (41.8 cm)
680GC	71395	29	12 in (30 cm)	17.5 in (44.5 cm)	12.4 in (31.5 cm)
	513122	32	14 in (35 cm)	19.7 in (50.0 cm)	14.7 in (37.3 cm)
695GC	553207	29	12 in (30 cm)	17.4 in (44.2 cm)	12.3 in (31.2 cm)
	73600	32	14 in (35 cm)	19.9 in (50.5 cm)	15 in (38.1 cm)
	71600	35	16 in (40 cm)	21.9 in (55.6 cm)	16.7 in (42.4 cm)
695F4	553208	25 F4	12 in (30 cm)	18.0 in (45.7 cm)	13.2 in (33.3 cm)
	525872	27 F4	14 in (35 cm)	19.9 in (50.5 cm)	15 in (38.1 cm)
	524490	29 F4	16 in (40 cm)	21.9 in (55.6 cm)	16.9 in (42.9 cm)
603/660GC	517689	25	10 in (25 cm)	14.8 in (37.6 cm)	10.8 in 27.3 cm)

* Subtract 3 inches when using SpeedHook®

Note: Cutting depth will increase up to 1 in (3 cm) as chain stretches