

MASONRY SAWS

14" and 20" Gasoline and Electric



EDCO

Equipment Development Co., Inc.

edcoinc.com
1-800-638-3326

SURFACE PREPARATION & PROFESSIONAL SAWING EQUIPMENT

Patented Fixed Engine Platform Prevents Burnout!

EDCO's fixed engine platform eliminates



low-oil situations that could lead to engine burnout. The engine is isolated from the cutting arm, which minimizes vibration and extends blade life.

Vacuum Shroud Ports Create Dust-Free Worksite!

EDCO's optional dust shroud can help you



control dry concrete and masonry dust and eliminate the environmental hazards of airborne particles.



14" Gasoline Masonry Saw



Model
BB-14G



Click or Scan
for video

Ideal for

- Professional masons, paver installers, paver manufacturers, landscape suppliers, masonry suppliers and rental stores.

Features

- 14" blade capacity
- Adjustable cutting head can be used manually or locked in a fixed position
- Unit includes a belt driven connectable and disconnectable water pump

Specifications

Power Options: *5.5HP, *6.5HP or *9HP

Length: 43" (109 cm) **Width:** 25" (64 cm)

Height: 37" (94 cm) **Weight:** 175 lbs. (79kg)

Blade Capacity: 14"

Water Feed: Belt driven water pump

Cutting Head: Gas shock return

14" Electric Masonry Saw



Model
BB-14E

Ideal for

- Professional masons, paver installers, paver manufacturers, landscape suppliers, masonry suppliers and rental stores.

Features

- 14" blade capacity
- Includes 115V submersible water pump with waterproof switch
- Adjustable cutting head can be used manually or locked in a fixed position
- Unit has a totally enclosed fan-cooled motor

Specifications

Power Options: 1.5HP(115 or 230V)

Length: 43" (109 cm) **Width:** 25" (64 cm)

Height: 32" (81 cm) **Weight:** 165 lbs. (75 kg)

Blade Capacity: 14"

Water Feed: Electric water pump

Cutting Head: Spring return

20" Gasoline Masonry Saw



Model
GMS-20

Ideal for

- Professional masons, paver installers, paver manufacturers, landscape suppliers, masonry suppliers and rental stores.

Features

- Freestanding model with 14" to 20" blade capacity
- Large-capacity, 3-stage air filter protects engine from wear
- Belt-driven diaphragm water pump is standard and can be disconnected when cutting dry

Specifications

Power Options: *9HP or *11HP

Length: 58.5" (149 cm) **Width:** 26" (66 cm)

Height: 75.5" (192 cm) **Weight:** 480 lbs. (218 kg)

Blade Capacity: 14"- 20"

Water Feed: Belt driven water pump

Cutting Head: Foot pedal spring return

20" Electric Masonry Saw



Model
MS-20

Ideal for

- Professional masons, paver installers, paver manufacturers, landscape suppliers, masonry suppliers and rental stores.

Features

- Freestanding model with 14" to 20" blade capacity
- Totally enclosed, fan cooled electric motor with waterproof switchbox
- Submersible water pump
- Thermal-protection shutoff

Specifications

Power Options: *5HP or *7.5HP

Length: 55" (140 cm)

Width: 26" (66 cm)

Height: 63" (160 cm)

Weight: 440 lbs. (200 kg)

Blade Capacity: 14" - 20"

Water Feed: Electric water pump

Cutting Head: Foot pedal Spring return

EDCO Diamond Blades

EDCO offers a full line of Diamond Blades for our Masonry Saws.

Request an EDCO Diamond Catalog or visit edcoinc.com and download your copy today!



GENERAL PURPOSE BLADES Cured Concrete & Masonry

STANDARD AND HIGH PERFORMANCE (WET OR DRY)
10", 14" & 20" Available



HARD MATERIAL BLADES Hard Cured Concrete

STANDARD AND HIGH PERFORMANCE (WET OR DRY)
10", 14", 20" & 22" Available



NET HORSEPOWER STATEMENT

*As rated by the engine manufacturer. The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE j1349 at 3600 rpm. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the opening speed of the engine in application, environmental conditions, maintenance, and other variables.